

## Chemical Safety Data Sheet MSDS / SDS

## Chlorotrimethylsilane

Revision Date:2024-12-21 Revision Number:1

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## Product identifier

Product name : Chlorotrimethylsilane  
CBnumber : CB4375627  
CAS : 75-77-4  
EINECS Number : 200-900-5  
Synonyms : TMSI,75-77-4

## Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : For R&D use only. Not for medicinal, household or other use.  
Uses advised against : none

## Company Identification

Company : Chemicalbook  
Address : Building 1, Huihuang International, Shangdi 10th Street, Haidian District, Beijing  
Telephone : 400-158-6606

## SECTION 2: Hazards identification

## GHS Label elements, including precautionary statements

Symbol(GHS)



Signal word

Danger

## Precautionary statements

P501 Dispose of contents/container to.....  
P406 Store in corrosive resistant/... container with a resistant inner liner.  
P405 Store locked up.  
P403+P235 Store in a well-ventilated place. Keep cool.  
P390 Absorb spillage to prevent material damage.  
P370+P378 In case of fire: Use ... for extinction.  
P310 Immediately call a POISON CENTER or doctor/physician.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continuerinsing.  
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P264 Wash skin thoroughly after handling.

P264 Wash hands thoroughly after handling.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P240 Ground/bond container and receiving equipment.

P234 Keep only in original container.

P233 Keep container tightly closed.

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

#### **Hazard statements**

H373 May cause damage to organs through prolonged or repeated exposure

H351 Suspected of causing cancer

H336 May cause drowsiness or dizziness

H335 May cause respiratory irritation

H331 Toxic if inhaled

H318 Causes serious eye damage

H314 Causes severe skin burns and eye damage

H312 Harmful in contact with skin

H303 May be harmful if swallowed

H302 Harmful if swallowed

H290 May be corrosive to metals

H226 Flammable liquid and vapour

H225 Highly Flammable liquid and vapour

---

## SECTION 3: Composition/information on ingredients

### **Substance**

Product name : Chlorotrimethylsilane

Synonyms : TMSi, 75-77-4

CAS : 75-77-4

EC number : 200-900-5

MF : C<sub>3</sub>H<sub>9</sub>ClSi

MW : 108.64

---

## SECTION 4: First aid measures

### **Description of first aid measures**

#### **General advice**

First aiders need to protect themselves. Show this material safety data sheet to the doctor

#### **If inhaled**

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

**In case of skin contact**

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

**In case of eye contact**

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.

**If swallowed**

If swallowed: give water to drink (two glasses at most). Seek medical advice immediately. In exceptional cases only, if medical care is not available within one hour, induce vomiting (only in persons who are wide awake and fully conscious), administer activated charcoal (20 - 40 g in a 10% slurry) and consult a doctor as quickly as possible. Do not attempt to neutralise.

**Most important symptoms and effects, both acute and delayed**

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

**Indication of any immediate medical attention and special treatment needed**

No data available

---

## SECTION 5: Firefighting measures

**Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO<sub>2</sub>) Dry powder

**Unsuitable extinguishing media**

Foam Water

**Special hazards arising from the substance or mixture**

Carbon oxides Hydrogen chloride gas silicon oxides Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors. Risk of dust explosion.

May not get in touch with: Water

Development of hazardous combustion gases or vapours possible in the event of fire. Forms explosive mixtures with air at ambient temperatures.


**Advice for firefighters**

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

**Further information**

Water hydrolyzes material liberating acidic gas which in contact with metal surfaces can generate flammable and/or explosive hydrogen gas. Remove container from danger zone and cool with water. Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

**NFPA 704**



<input type="checkbox"/>	HEALTH	3	Short exposure could cause serious temporary or moderate residual injury (e.g. <a href="#">liquid hydrogen</a> , <a href="#">sulfuric acid</a> , <a href="#">calcium hypochlorite</a> , hexafluorosilicic acid)
<hr/>			
<input type="checkbox"/>	FIRE	3	Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions. Liquids having a flash point below 22.8 °C (73 °F) and having a boiling point at or above 37.8 °C (100 °F) or having a flash point between 22.8 and 37.8 °C (73 and 100 °F). (e.g. gasoline, <a href="#">acetone</a> )
<hr/>			
<input type="checkbox"/>	REACT	2	Undergoes violent chemical change at elevated temperatures and pressures, reacts violently with water, or may form explosive mixtures with water (e.g. white phosphorus, <a href="#">potassium</a> , <a href="#">sodium</a> )
<hr/>			
<input type="checkbox"/>	SPEC. HAZ.	W	

## SECTION 6: Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

### Environmental precautions

Do not let product enter drains. Risk of explosion.

### Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g.

Chemisorb?). Dispose of properly. Clean up affected area.

### Reference to other sections

For disposal see section 13.

## SECTION 7: Handling and storage

### Precautions for safe handling

#### Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols. Keep workplace dry. Do not allow product to come into contact with water.

#### Advice on protection against fire and explosion

Flash back possible over considerable distance. Container explosion may occur under fire conditions. **Advice on protection against fire and explosion**

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

### **Hygiene measures**

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

### **Conditions for safe storage, including any incompatibilities**

#### **Storage conditions**

Store under inert gas.

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons.

Never allow product to get in contact with water during storage. Store under inert gas.

#### **Specific end use(s)**

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

---

## **SECTION 8: Exposure controls/personal protection**

### **control parameter**

#### **Hazard composition and occupational exposure limits**

Does not contain substances with occupational exposure limits.

#### **Exposure controls**

##### **Personal protective equipment**

###### **Eye/face protection**

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles

###### **Skin protection**

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

Full contact Material: Viton?

Minimum layer thickness: 0,7 mm Break through time: 480 min

Material tested: Vitoject? (KCL 890 / Aldrich Z677698, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other

substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

Splash contact Material: Chloroprene

Minimum layer thickness: 0,65 mm Break through time: 120 min Material tested: KCL 720 Camapren?

###### **Body Protection**

Flame retardant antistatic protective clothing.

#### Respiratory protection

Recommended Filter type: Filter type B

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

#### Control of environmental exposure

Do not let product enter drains. Risk of explosion.

---

## SECTION 9: Physical and chemical properties

### Information on basic physicochemical properties

Appearance	liquid
Odour	No data available
Odour Threshold	No data available
pH	No data available
Melting point/freezing point	Melting point/range: -40 °C - lit.
Initial boiling point and boiling range	57 °C - lit.
Flash point	-28 °C - closed cup
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Upper/lower flammability or explosive limits	Upper explosion limit: 46 %(V) Lower explosion limit: 1,5 %(V)
Vapour pressure	278,6 hPa at 20 °C
Vapour density	3.7 (vs air)
Relative density	0.8536 (27°C)
Water solubility	0,995 g/l at 24 °C - OECD Test Guideline 105
Partition coefficient: n-octanol/water	log Pow: 1,19 at 25 °C - Bioaccumulation is not expected.
Autoignition temperature	407 °C at 1.013 hPa - ASTM E-659
Decomposition temperature	No data available
Viscosity	Viscosity, kinematic: No data available Viscosity, dynamic: No data available
Explosive properties	No data available
Oxidizing properties	No data available

### Other safety information

No data available

---

## SECTION 10: Stability and reactivity

### Reactivity

Vapors may form explosive mixture with air. Reacts violently with water.

## Chemical stability

sensitive to moisture

## Possibility of hazardous reactions

Violent reactions possible with:

Alcohols Ammonia Bases

Oxidizing agents Acetone

Esters Ketones Aldehydes Strong acids Amines Water

Possible formation of:

Hydrogen chloride gas

## Conditions to avoid

Water hydrolyzes material liberating acidic gas which in contact with metal surfaces can generate flammable and/or explosive hydrogen gas.

Humid air

Heat, flames and sparks. Extremes of temperature and direct sunlight. Exposure to moisture.

Warming. Moisture.

## Incompatible materials

Metals, with water(generation of hydrogen)

## Hazardous decomposition products

In the event of fire: see section 5

---

# SECTION 11: Toxicological information

## Information on toxicological effects

### Acute toxicity

LD50 Oral - Rat - male - < 212 mg/kg (OECD Test Guideline 401)

LC50 Inhalation - Rat - male and female - 1 h - 4257 ppm (OECD Test Guideline 403)

Remarks: (calculated)

LD50 Dermal - Rabbit - male and female - 1.513 mg/kg (OECD Test Guideline 402)

### Skin corrosion/irritation

Skin - Rabbit

Result: Causes burns. - 4 h (OECD Test Guideline 404)

### Serious eye damage/eye irritation

Eyes - Rabbit

Result: Causes burns. (Draize Test)

Causes serious eye damage.

### Respiratory or skin sensitization

No data available

### Germ cell mutagenicity

Test Type: Ames test

Test system: Escherichia coli/Salmonella typhimurium Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471

Result: negative

Test Type: Mutagenicity (mammal cell test): chromosome aberration. Test system: Mouse lymphoma test

Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 473

Result: negative

Test Type: In vitro mammalian cell gene mutation test Test system: Mouse lymphoma test

Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 476

Result: negative

Test Type: Chromosome aberration test Species: Rat

Cell type: Bone marrow

Application Route: Intraperitoneal injection Method: OECD Test Guideline 475

Result: negative

### **Carcinogenicity**

No data available

### **Reproductive toxicity**

No data available

### **Specific target organ toxicity - single exposure**

No data available

### **Specific target organ toxicity - repeated exposure**

No data available

### **Aspiration hazard**

No data available

### **Toxicity**

LD50 orally in Rabbit: 4868 mg/kg LD50 dermal Rabbit 1530 mg/kg

---

## SECTION 12: Ecological information

### **Toxicity**

#### **Toxicity to fish**

semi-static test LC50 - Oncorhynchus mykiss (rainbow trout) - 271 mg/l - 96 h

(OECD Test Guideline 203)

#### **Toxicity to daphnia and other aquatic invertebrates**

semi-static test EC50 - Daphnia magna (Water flea) - 124 mg/l - 48 h

(OECD Test Guideline 202)

#### **Toxicity to algae**

static test EC50 - Pseudokirchneriella subcapitata - 566 mg/l - 72 h (OECD Test Guideline 201)

#### **Toxicity to bacteria**

EC50 - activated sludge - 6.670 mg/l

(OECD Test Guideline 209)

### **Persistence and degradability**

Biodegradability aerobic - Exposure time 28 d



Result: 0 % - Not readily biodegradable. (OECD Test Guideline 310)

### **Bioaccumulative potential**

No data available

### **Mobility in soil**

No data available

### **Results of PBT and vPvB assessment**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### **Other adverse effects**

No data available

---

## SECTION 13: Disposal considerations

### **Waste treatment methods**

#### **Incompatibilities**

Incompatible with oxidizers; contact may cause fires or explosions. Keep away from alkaline materials, strong bases, strong acids, oxoacids, epoxides. Chlorosilanes react vigorously with bases and both organic and inorganic acids generating toxic and/or flammable gases. Attacks metals in the presence of moisture. Vigorous reaction with aluminum powder.

#### **Product**

See [www.retrologistik.com](http://www.retrologistik.com) for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

#### **Waste Disposal**

Do not discharge into drains or sewers. Use a licensed disposal contractor to an approved landfill.

---

## SECTION 14: Transport information

### **UN number**

ADR/RID: 1298 IMDG: 1298 IATA: 1298

### **UN proper shipping name**

ADR/RID: TRIMETHYLCHLOROSILANE IMDG: TRIMETHYLCHLOROSILANE

IATA: Trimethylchlorosilane

Passenger Aircraft: Not permitted for transport

14.3	Transport hazard class(es) ADR/RID: 3 (8) IMDG: 3 (8)	IATA: 3 (8)
14.4	Packaging group ADR/RID: II IMDG: II	IATA: II
14.5	Environmental hazards	

---

## SECTION 15: Regulatory information

### Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Regulations on the Safety Management of Hazardous Chemicals

China Catalog of Hazardous chemicals 2015:Listed. website: <https://www.mem.gov.cn/>

#### Measures for Environmental Management of New Chemical Substances

Vietnam National Chemical Inventory:Listed. website: <https://chemicaldata.gov.vn/>

United States Toxic Substances Control Act (TSCA) Inventory:Listed. website: <https://www.epa.gov/>

Philippines Inventory of Chemicals and Chemical Substances (PICCS):Listed. website: <https://emb.gov.ph/>

New Zealand Inventory of Chemicals (NZIoC):Listed. website: <https://www.epa.govt.nz/>

Korea Existing Chemicals List (KECL):Listed. website: <http://ncis.nier.go.kr>

European Inventory of Existing Commercial Chemical Substances (EINECS):Listed. website: <https://echa.europa.eu/>

EC Inventory:Listed.

Chinese Chemical Inventory of Existing Chemical Substances (China IECSC):Listed. website: <https://www.mee.gov.cn/>

---

## SECTION 16: Other information

### Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

CAS: Chemical Abstracts Service

EC50: Effective Concentration 50%

IATA: International Air Transportation Association

IMDG: International Maritime Dangerous Goods

LC50: Lethal Concentration 50%

LD50: Lethal Dose 50%

RID: Regulation concerning the International Carriage of Dangerous Goods by Rail

STEL: Short term exposure limit

TWA: Time Weighted Average

### References

**[1]** CAMEO Chemicals, website: <http://cameochemicals.noaa.gov/search/simple>

**[2]** ChemIDplus, website: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>

**[3]** ECHA - European Chemicals Agency, website: <https://echa.europa.eu/>

**[4]** eChemPortal - The Global Portal to Information on Chemical Substances by OECD, website:

[http://www.echemportal.org/echemportal/index?pageID=0&request\\_locale=en](http://www.echemportal.org/echemportal/index?pageID=0&request_locale=en)

**[5]** ERG - Emergency Response Guidebook by U.S. Department of Transportation, website: <http://www.phmsa.dot.gov/hazmat/library/erg>

**[6]** Germany GESTIS-database on hazard substance, website: <http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp>

**[7]** HSDB - Hazardous Substances Data Bank, website: <https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm>

【8】 IARC - International Agency for Research on Cancer, website: <http://www.iarc.fr/>

【9】 IPCS - The International Chemical Safety Cards (ICSC), website: <http://www.ilo.org/dyn/icsc/showcard.home>

【10】 Sigma-Aldrich, website: <https://www.sigmaaldrich.com/>

### **Other Information**

Reacts violently with fire extinguishing agents such as water. The symptoms of lung oedema often do not become manifest until a few hours have passed and they are aggravated by physical effort. Rest and medical observation are therefore essential. Immediate administration of an appropriate inhalation therapy by a doctor, or by an authorized person, should be considered. Toxicological properties are inferred from those of Methylchlorosilane (ICSC 0297).

#### **Disclaimer:**

The information in this MSDS is only applicable to the specified product, unless otherwise specified, it is not applicable to the mixture of this product and other substances. This MSDS only provides information on the safety of the product for those who have received the appropriate professional training for the user of the product. Users of this MSDS must make independent judgments on the applicability of this SDS. The authors of this MSDS will not be held responsible for any harm caused by the use of this MSDS.